











Multiscreen 1%, 5%, 10%











5%





Multiscreen 1%, 5%, 10%


			Multiscreen 1%	Multiscreen 5%	Multiscreen 10%
Composition	DIN 60 001		Glass fibre, PVC coated (36% Glas fibre, 64% PVC)		
Fabric weight (g/m ²)	DIN EN 12127		450	410	350
Fabric thickness (mm)	DIN ISO 2286-3		0.55	0.55	0.55
Fabric width (cm)			250	310	310
Louvre width (mm)			-	89, 127	-
Eco-tex Standard 100	LYC 05-3663 ASQUAL		Yes	Yes	Yes
Flame retardant			M1 (NF P 92501-7)	M1 (NF P 92501-7)	M1 (NF P 92501-7)
Colour fastness	DIN ISO 105-B02		7-8	7-8	7-8
Applicable in humid areas			Yes	Yes	Yes
Washing instructions					
Opening factors 1/5/10 %: These coefficients indicate the openings in the fabric.					

Solar and optical coefficients (DIN EN 14501) All coefficients may have a tolerance of +/- 5%.

Colour	Multiscreen 1%			Multiscreen 5%							Multiscreen 10%								
	0702	0730	3001	0202	0207	0220	0707	2020	3001	3006	3030	0202	0207	0220	0707	2020	3001	3006	3030
	14	5	5	21	17	21	17	21	6	6	6	27	24	25	22	24	15	11	14
	47	24	15	68	54	61	35	53	10	6	5	63	52	58	36	51	10	6	5
	39	71	80	11	29	18	48	26	84	88	89	10	24	17	42	25	75	83	81
	0.41	0.48	0.51	0.35	0.39	0.37	0.45	0.40	0.53	0.54	0.54	0.37	0.40	0.38	0.45	0.40	0.53	0.54	0.54
	0.27	0.28	0.29	0.25	0.26	0.25	0.28	0.26	0.29	0.30	0.30	0.25	0.26	0.26	0.28	0.26	0.30	0.30	0.30
	12	4	5	20	14	18	15	18	6	6	6	26	22	23	20	21	14	11	14
	11	3	1	15	9	14	10	13	1	1	1	16	14	12	8	9	2	1	1
	1	1	4	5	5	4	5	5	5	5	5	10	8	11	12	12	12	10	13

 Solar transmission (%)

 Solar reflectance (%)

 Solar absorption (%)

 Total g-value (Glass g-value: 0,59; 1,2W/m²/K)

 Total g-value (Glass g-value: 0,32; 1,1W/m²/K)

 Visible light transmission (%)

 Vertical/difuse Lighttransmission

 Vertical/vertical Lighttransmission

Multiscreen 1%



0702



0730



3001

Multiscreen 5%, Multiscreen 10%



0202



0220



2020



0207



0707



3001



3006



3030