

Electrically Operated Curtain Track Systems



This brochure contains colour illustrations and a summary specification for each of the systems in this product group to assist your clients in making their choice.

Silent Gliss has developed the widest, most efficient and reliable range of electrically operated curtain track systems – purpose designed for conference rooms, theatres, stages and auditoriums as well as for all domestic and contract locations.



Silent Gliss Autoglides 5070, 5080, 5080AR ▶
For light to medium weight domestic use only.

White profile, easy wall or ceiling mounted, delivered ready to fit. Maximum length is 5m with a maximum curtain weight of 15kg. No pre-wiring necessary. Cannot be bent. Choice of operating methods – via the Dawn and Dusk sensor (5070), which opens the curtains in the morning and closes them at night, using a Timer Unit (5080) which allows pre-programming of opening and closing times, or, by Remote Control (5080AR) which has a remote control handset as well as the Timer Unit.

Autoglides is supplied made-to-measure and cannot be cut down at a later date.



◀ Silent Gliss 5400
Single channel for domestic and medium/heavy weight contract use.

Smooth, silent operation with roller gliders. Ceiling, recess or wall fix. Can be bent to a minimum radius of 250mm. Profile available in silver, white, bronze and black as standard. Available with or without integrated radio receiver for use with Silent Gliss radio control System 0450. Suitable for use with Wave curtain heading system.

Silent Gliss 5420 ▶
Dual channel for domestic and medium/heavy contract use.

Smooth, silent operation.

Dual channel allows for unlimited curtain overlap with without the need for an overlap arm. Option of manual override in case of power failure or where there is a risk of the curtain being operated by hand due to product unfamiliarity (e.g. hotels). Asymmetric stacks available. Wall or ceiling fix. Available with or without integrated radio receiver for use with Silent Gliss radio control System 0450. Suitable for use with Wave curtain heading system. Can be bent to a minimum radius of 500mm.



◀ Silent Gliss 5300
For small stages and theatres, conference rooms, presentation and audio visual rooms.

Smooth, silent operation with roller gliders. Up to 15 tracks to be connected and operated together without the use of relays. Versatile bending possibilities. Multiple and asymmetrical stacking.

Silent Gliss Ltd
 Head Office and Factory
 Pyramid Business Park
 Poorhole Lane, Broadstairs
 Kent CT10 2PT

Tel: 00 44 (0)1843 863571
 Fax: 00 44 (0)1843 864503
 E-mail: sales@silentgliss.co.uk
www.silentgliss.co.uk



Year Guarantee

